Attorney Docket No.:

DMBC-0007

Inventors:

Harry C. Morris

Serial No.: Filing Date:

10/840,052 May 6, 2004

Page 3

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of the Claims:

Claim 1-2: (canceled)

Claim 3: (previously presented) The friction resistant coater or doctor blade of claim 10 wherein the protective layer comprises low phosphorous electroless nickel.

Claim 4: (previously presented) The friction resistant coater or doctor blade of claim 10 wherein the protective layer is between 0.0002 to 0.0009 inches thick.

Claim 5: (previously presented) The friction resistant coater or doctor blade of claim 10 wherein the blade-shaped substrate base comprises carbon strip steel, stainless steel, stainless alloy or bronze.

Claim 6: (previously presented) The friction resistant coater or doctor blade of claim 10 wherein the edge is beveled.

Claim 7: (previously presented) The friction resistant coater or doctor blade of claim 10 wherein the edge is square.

Attorney Docket No.:

DMBC-0007

Inventors:

Harry C. Morris

Serial No.: Filing Date:

10/840,052 May 6, 2004

Page 4

Claim 8: (currently amended) A method of producing a friction resistant coater or doctor blade for applying inks and coatings to paper and packaging comprising:

applying a protective layer of chromium, low phosphorus nickel or electroplated hard chrome to an edge of a blade-shaped substrate base; and

heat treating said protective layer on the bladeshaped substrate for an amount of time suitable to provide a Rockwell C hardness measurement of greater than 70 to said protective layer; and

packaging the blade shaped substrate in a coiled roll.

Claim 9: (original) The method of claim 8 wherein the protective layer comprises low phosphorous electroless nickel.

Claim 10: (currently amended) A friction resistant coater or doctor blade for applying inks and coatings to paper and packaging comprising a blade-shaped substrate base with an edge which allows coating or ink to be evenly applied to paper or board and a protective layer of chromium, low phosphorus nickel or electroplated hard chrome applied to at least the edge of said blade-shaped substrate, said protective layer heat treated after application to at least the edge of the blade-shaped substrate base to provide a Rockwell C hardness of greater than 70, wherein said friction resistant coater or doctor blade is packaged in a coiled roll.